



## >> Specification

Mode/specs	AZL18-LX10C	AZL18-LX10CZ
	AZL18-LS10C	AZL18-LS10CZ
	X-down discharge,S-up discharge	
Electrial Source (V/Hz)	220/50	200~277/50~60
Power(kw)	1.5	1.5
Motor	220V/50Hz 3-phase	DC ( 220V 3-phase)
Rated Currency(A)	11	9
Photo		
Airflow(m³/h)	18000	18000
Fan Type	Centrifugal	Centrifugal
Fan Speed	Multi-speed,Inverter	Multi-speed,Inverter
Pressure(Pa)	163	163
Vent Size (LXH)(mm)	650x650	650x650
Noise(dBA)	≤70	≤69
Dimension (LWXH)(mm)	1150x1150x950(down) 1150x1150x982(up)	1150x1150x950(down) 1150x1150x982(up)
Pad Size (LWXH)(mm)	620x830x75 620x830x100	620x830x75 620x830x100
Net Weight (±3kg)	87	79
Operation Weight(kg)	117	107
Controller	LCD	LCD
Pre-dust Filter	Optional	Optional
Exhaust	Optional	Optional
Pre-cooling	Optional	Optional
Group-control	Optional	Optional
Damper	Optional	Optional
Tem&hum Control	Optional	Optional
QTY/Full(40HQ)	40(down/up)	40(down/up)
QTY/SKD(40HQ)	45(down/up)	45(down/up)

# SALES CONTACT



[www.airmax-hvac.com](http://www.airmax-hvac.com)



080-614-4944, 063-268-8080



@airmax (Line Official)



[windcontrol.info@gmail.com](mailto:windcontrol.info@gmail.com)



Address

เลขที่ 56/392 หมู่ที่ 12  
ตำบลศีรษะจรเข้น้อย  
อำเภอบางเสาธง  
จังหวัดสมุทรปราการ  
10540